

Styrene Butadiene Rubber (SBR)

Commonly used for tires, conveyor belts, and chutes, SBR (styrene butadiene rubber) is harder and offers better abrasion resistance than natural rubber. It is also known as skirtboard. All meet ASTM material standards for rubber.

TECHNICAL DATA SHEET | (EFFECTIVE 24FEB25)

75 Durometer, SBR		
PHYSICAL PROPERTY	UNIT	VALUE
Material	-	SBR
Shape	-	Sheet and Bar
Texture	-	Smooth
Thickness	in	1/16
Thickness Tolerance	in	-0.016 to 0.016
Width	in	12
Width Tolerance	in	-0.25 to 0.25
Backing Type	-	Plain
For Outdoor Use	-	No
Temperature Range	°F	-20 to 170
Tensile Strength	psi	700
Color	-	Black
Durometer	-	75A (Hard)
Durometer Tolerance	-	-5 to 5
Specifications Met	-	ASTM D1330, ASTM D2000 4 AA 707 A13 Z1 Z2 Z3, SDS
RoHS	-	RoHS 3 (2015/863/EU) Compliant
REACH	-	REACH (EC 1907/2006) (01/23/2024, 240 SVHC) Compliant
DFARS	-	Specialty Metals COTS-Exempt
Country of Origin	-	United States
USMCA Qualifying	-	No
Schedule B	-	400811.0000
ECCN	-	EAR99